

HUSTLER® COMMERCIAL ZERO-TURN MOWER

# SUPER 104

## 104" WIDTH OF CUT MAKES BIG JOBS EASY



### WIDE-AREA MOWER WITH ZERO-TURN MANEUVERABILITY

Hustler's Super 104 can easily handle acres of work. Offering a 104" width of cut, zero-turn precision and an impressive 11 mph (18kph) speed, this machine is in a class by itself. Its industrial-grade HyperDrive® Hydro System is engineered to handle thousands of hours of the toughest jobs out there. Transporting is easy as it folds into an 80" transport width. A Grammar suspension seat, welded steel deck and 45.5 litre fuel capacity provides comfort, durability, and more performance than your average zero-turn mower.




#### HYPERDRIVE® HYDRO SYSTEM

Features industrial-grade pumps and motors to handle tough jobs and long days in stride.



#### 104" WIDTH OF CUT

Widest and most productive commercial zero-turn available.



#### 80" TRANSPORT WIDTH

Fits most trailers making it easy to transport from job-to-job.



LIMITED  
LIFETIME WARRANTY  
ON THE FRAME

LIMITED WARRANTY  
2 YEAR NO HOUR LIMIT

OR

LIMITED WARRANTY  
5 YEAR 500 HOUR

Find A Hustler Dealer  
visit [www.hustlermowers.co.nz](http://www.hustlermowers.co.nz)

## ENGINE

Manufacturer	Vanguard
HP	37HP* - Vanguard BIG BLOCK™ EFI * Per SAE J1995
Displacement	993 cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	5 year (Vanguard only)

## DRIVE SYSTEM

Type	Dual hydrostatic
Pumps	Danfoss DDC20
Wheel Motors	Parker TG0360
Hydraulic Lines	Stainless steel Parker seal loc technology
Reservoir Capacity	3 gallons (11.4L)
Speed	11 mph (18 kph)
Parking Brakes	Patented automatic

## DECKS

Cutting Width	Rear discharge: 104"
Cutting Heights	1"- 5.5"
Deck Lift	Hydraulic powered
Depth	5.5"
Blades	5
Blade Length	1 - 23.86" x 2.50" x .20" CW 1 - 23.86" x 2.50" x .20" CCW 1 - 20.50" x 2.50" x .20" CCW 2 - 20.50" x 2.50" x .20" CW
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1 per deck
Drive	Electric PTO clutch
Construction	11 ga. welded steel
Spindle Mounts	Reinforced 7 ga. doubler
Impact/Trim Areas	1.5" x .375" steel bar protector

## CONSTRUCTION

Frame	1.5" x 3.0" x .187" steel
Front Caster Wheels	Mounted tapered greasable bearings
Front Caster Forks	Fabricated 1/2" steel

## GENERAL

Seat	Grammer suspension seat, isolator platform
Fuel Capacity	12 gallons (45.5L)
Cup Holder	Yes
Front Tire	15 x 6.0 - 6
Drive Tire	26 x 12 - 12

## DIMENSIONS

Weight	2500 lbs (1134 kg)
Height w/rops up	71.5" (1.82m)
Height w/rops Folded	54" (1.37m)
Length	95.5" (2.43m)
Width	106.1" (2.69m) wings down 80.0" (2.03m) wings up at gauge wheels 72.5" (1.84m) wings up at deck base
Tire Width	60.3" (1.53m)

## PRODUCTIVITY\*

Acres Per Hour	9.24
----------------	------

## OPTIONAL ACCESSORIES

Mulch kit  
Steering lever extension kit  
Light kit  
Anti-scalp kit  
Flasher kit  
Beacon kit  
Flex Forks™  
Hitch kit

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

## SUPER 104 | AT A GLANCE

- Widest and most productive commercial zero-turn available
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- Patented automatic park brake
- Wide area mower with 80" transport width – fits most trailers
- 11 mph (18 kph) speed
- 12 gallon (45.5L) fuel capacity
- Hydraulic powered deck height adjustment
- Grammer suspension seat with isolator platform
- HyperDrive® industrial hydro system – mow in tough conditions without losing performance



Visit [hustlermowers.co.nz](http://hustlermowers.co.nz)  
and try our compare products tool!