




# FLIP-UP



#### PREMIUM SEAT

Premium bolstered seat with built in lumbar support



#### AUTO DECK HEIGHT ADJUSTMENT

Raises and lowers deck at the push of a button



#### WELDED STEEL DECK

11 ga. welded fabricated steel deck adds durability & extends mower's life

## QuickFlip

TECHNOLOGY

Raises and lowers deck for easy access to blades.

# FLIP-UP

ENGINE	
Manufacturer	Kawasaki® FR series
HP	48", 54" deck: 23HP - FR691 (Per SAE J1995)
Displacement	726cc
Cooling	Air cooled
Engine Warranty	3 year
DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Hydro-Gear® ZT2800
Speed	Up to 11kph
Parking Brakes	Patented automatic
DECKS	
Cutting Width	Side discharge: 48", 54"
Cutting Height	1.5" - 4.5"
Deck Lift	Electric/hydraulic actuated
Depth	4.5"
Blades	3
Blade Length	48" deck: 16.50" x 2.5" x 0.203"    54" deck: 18.50" 2.5" x 0.203"
Blade Tip Speed	48" deck: 18,500 54" deck: 18,800
Spindles	Aluminium with 1" shafts and double lip sealed ball bearings
Drive	Electric PTO clutch
Construction	Fabricated 11 ga. steel
Spindle Mounts	Reinforced 7 ga. steel
Impact/Trim Areas	3/8" x 1" steel bar
CONSTRUCTION	
Frame	1.5" x 1.5" steel tubing
Eng/Trans. Frame	7 gauge frame rails
Front Axle	Fabricated with sealed ball bearings
Front Caster Wheels	Commercial duty steel roller bearings, greasable
Front Caster Forks	Fabricated 1/4" steel
GENERAL	
Seat	Premium bolstered seat with built-in lumbar support
Fuel Capacity	11.4 Litres
Cupholder	Yes
Front Tyre	11.4" pneumatic
Drive Tyre	48": 20 x 8 - 10 BigBite™    54": 20 x 10 - 10 BigBite™
DIMENSIONS	
Weight	48" deck: 342kg    54" deck: 349kg
Height	1.07m
Length	1.76m
Width w/Chute	48" deck: 1.24m    54" deck: 1.39m
Tyre width	1.10m
Trim Side	48" deck: 0.05m    54" deck: 0.10m
ACCESSORIES	
	Grass bagger (non-powered 5.4 Bushels), Steering extension kit, Mulch kit, FlexForks®
PRODUCTIVITY*	
Acres per hour	48" deck: 2.71    54" deck: 3.01

IDEAL FOR UP TO

**3**  
ACRES

 VISIT [HUSTLERMOWERS.CO.NZ](http://HUSTLERMOWERS.CO.NZ)  
and try our compare products tool

Specifications are subject to change without notice  
\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain  
NZV1 11/2020

